

	Bestellnummer Materialnummer Order number Item	Kunden-Bez. Customer title	Wicklung Winding WV No.	Nennweite Orifice 1)		Druck Pressure 1)		Umgebungstemp. Ambient temp.		Temperaturklasse Temperature class	Gruppe Group	Ex i Bescheinigte Höchstwerte			Bemessungsstrom Rated current [mA]	Ex m		rel. Einschaltdauer Duty ratio [%]				
				Einlass Inlet [mm]	Auslass Outlet [mm]	min [bar]	max [bar]	min [°C]	max [°C]			Strom Current I _i [mA]	Spannung Voltage U _i [V]	Leistung Power P _i [W]		Nennspannung Nominal voltage			Frequenz Frequency [Hz]	Spannungstol. Voltage tol.		Kabellänge Cable length [m]
																DC [V]	AC [V]			- [%]	+ [%]	
	108-030-1160		5146	0,8	1,0	0	8	-40	50	T6	IIC	115	28						100			
	108-030-1162		5146	0,8	1,0	0	8	-40	85	T4	IIC	115	28						100			
X	108-030-1161		7210	0,6	0,8	0	8	-40	50	T6	IIC	115	28						100			
Bemerkung / Notice				Schutzvermerk ISO 16016 beachten Observe protection note ISO 16016							Datum / Date		Name		Benennung							
1) bezüglich NM Ankersystem 1) regarding NM armature assembly											Gezeichnet Drawn		05.12.2012		SD		Technische Daten Magnetspule Ex Technical Data Solenoid coil Ex					
											Geprüft Checked		17/12/2015		fu							
				3 26560 09.12.2015 SaK																		
				Ind Rev Änderung Change Datum Date Name By																		
				Ersatz für/Replacement for:																		
											Kunde Customer		nassmagnet		Freigabe Nr.		22300					
											Ident.-Nr. ID-No.		108-030-0246		Blatt Sheet		1/1					