

SAP TIM

Bestellnummer Materialnummer Order number Item	Kunden-Bez. Customer title	Wicklung Winding WV No.	Nennweite Orifice 1)		Druck Pressure 1)		Umgebungstemp. Ambient temp.		Widerstand Resistance 20 °C nominal (± 8 %) [Ω]	Spannungstol. Voltage tolerance		Spannung Voltage [V]	AC			DC		rel. Einschaltdauer Duty ratio [%]		
			Einlass Inlet [mm]	Auslass Outlet [mm]	min [bar]	max [bar]	min [°C]	max [°C]		- [%]	+ [%]		Frequenz Frequency [Hz]	Halteleistung Holding power [VA]	Spannung Voltage [V]	Leistung Power [W]				
113-030-0026		5751	2,0	2,5	0	10	-20	50	94,5	10	10				24	6,1	100			
113-030-0027		5752	2,5	3,0	0	10	-20	50	52,5	10	10				24	11,0	100			
113-030-0028		5753	3,0	3,5	0	10	-20	50	38,5	10	10				24	15,0	100			
113-030-0029		5756	2,0	2,5	0	10	-20	50	9,6	10	10	24 24	50 60	10,8 9,6			100			
113-030-0030		5758	2,5	3,0	0	10	-20	50	977	10	10				110	12,4	100			
113-030-0031		5759	2,5	3,0	0	10	-20	50	710	10	10	240 240	50 60	17,9 15,6			100			
113-030-0033		5761	2,0	2,5	0	10	-20	50	890	10	10	220 240	50 60	10,8 11,4			100			
113-030-0034		5762	2,5	3,0	0	10	-20	50	560	10	10	220 240	50 60	18,1 18,9			100			
113-030-0035		5763	3,0	3,5	0	10	-20	50	497	10	10	220 240	50 60	22,0 23,2			100			
113-030-0036		5764	2,0	2,5	0	10	-20	50	212	10	10	110 120	50 60	11,1 11,7			100			
113-030-0037		5765	2,5	3,0	0	10	-20	50	140	10	10	110 120	50 60	17,6 18,3			100			
113-030-0038		5766	3,0	3,5	0	10	-20	50	110	10	10	110 120	50 60	24,8 26,1			100			
113-030-0039		5767	2,5	3,0	0	10	-20	50	6,1	10	10	24 24	50 60	17,9 15,6			100			
113-030-0040		5768	3,0	3,5	0	10	-20	50	5,8	10	10	24 24	50 60	21,8 19,4			100			
Bemerkung / Notice 1) bezüglich NM Ankersystem 1) regarding NM armature assembly			Schutzvermerk ISO 16016 beachten Observe protection note ISO 16016				Datum / Date		Name		Benennung Title Technische Daten Magnetspule Technical Data Solenoid Coil									
			Gezeichnet Drawn		17.05.2006		POe													
			Geprüft Checked		25.04.2022		Kunze													
			5		31310		23.03.2022		MRo						Kunde Customer nass magnet				Freigabe Nr. 13253	
			Ind Rev		Änderung Change		Datum Date		Name By						Ident.-Nr. ID-No. 113-030-0310				Blatt Sheet 1/2	
			Ersatz für/ Replacement for: 0543 00.1-00																	

Bestellnummer Materialnummer Order number Item	Kunden-Bez. Customer title	Wicklung Winding WV No.	Nennweite Orifice 1)		Druck Pressure 1)		Umgebungstemp. Ambient temp.		Widerstand Resistance 20 °C nominal (± 8 %) [Ω]	Spannungstol. Voltage tolerance		Spannung Voltage [V]	AC		DC		rel. Einschaltdauer Duty ratio [%]							
			Einlass Inlet [mm]	Auslass Outlet [mm]	min [bar]	max [bar]	min [°C]	max [°C]		- [%]	+ [%]		Frequenz Frequency [Hz]	Halteleistung Holding power [VA]	Spannung Voltage [V]	Leistung Power [W]								
113-030-0042		5780	1,3	1,5	0	10	-20	50	285	10	10	110 120	50 60	7,8 8,0	24	2,0	100							
113-030-0043		5827	3,0	3,5	0	10	-20	50	18,3	10	10	48 48	50 60	26,2 23,2			100							
113-030-0047		5756	3,0	3,5	0	10	-20	50	9,6	10	10				12	15,0	100							
113-030-0049		6869	3,0	3,5	0	10	-20	50	117,7	10	10	110 110	50 60	21,7 19,2			100							
113-030-0050		5762	3,0	3,5	0	10	-20	50	560	10	10	230 230	50 60	21,4 19,0			100							
113-030-0051		5777	3,0	3,5	0	10	-20	50	3370	10	10				220	14,4	100							
113-030-0052		5754	2,5	3,0	0	10	-20	50	24	10	10	48 48	50 60	19,0 16,6			100							
113-030-0053		5759	3,0	3,5	0	10	-20	50	710	10	10				110	17,0	100							
113-030-0278		5754	2,0	2,5	0	10	-20	50	24	10	10	42 42	50 60	13,4 11,9	12	6,0	100							
113-030-0359		5755	2,5	3,0	0	10	-20	50	14,4	10	10				12	10,0	100							
Bemerkung / Notice 1) bezüglich NM Ankersystem 1) regarding NM armature assembly			Schutzvermerk ISO 16016 beachten Observe protection note ISO 16016				Datum / Date		Name		Benennung Title Technische Daten Magnetspule Technical Data Solenoid Coil													
							Gezeichnet Drawn		17.05.2006									POe						
							Geprüft Checked		25.04.2022									Kunze						
			5		31310		23.03.2022		MRo						Kunde Customer				nass magnet		Freigabe Nr.		13253	
			Ind Rev		Änderung Change		Datum Date		Name By						Ident.-Nr. ID-No.				113-030-0310				Blatt Sheet	
			Ersatz für/ Replacement for:				0543 00.1-00																	